

Xtreme / X2


Stoffgruppe 1

mauser  [®]
SitzKultur



martinique

YS004




positive

AK 019




algebra

AK 005




bonaire

YS 172




maths

AK 007



formula

AK 017



havana

YS 009



costa

YS 026



panama

YS 079

Xtreme / X2

Stoffgruppe 1



D

Zusammensetzung

100% post-consumer recycelten Polyester

Umweltfreundlich

Nach Zertifikat EU Ecolabel
Nach Zertifikat OEKO-TEX® Standard 100
Nach Zertifikat Indoor Advantage™ Gold
Hergestellt aus 100% recycelten Polyester
Nicht schwermetallhaltige Farbstoffe

Breite

140 cm nutzbare Breite

Gewicht

310 g/m² ±5% [435 g/lfd.m ±5%]

Scheuerfestigkeit

Schwerer Objekteinsetz / 10 Jahre Garantie
Extern zertifiziert mit <100,000 Scheuertouren
Martindale

Feuersicherung

EN 1021 - 1 (Zigarettentest)
EN 1021 - 2 (Streichholztest)
BS 7176 Low Hazard
BS 5852 Ignition Source 5
BS 7176 Medium Hazard
DIN 4102 B1
NF D 60-013
ÖNORM B 3825 & A 3800-1 – gültig für Xtreme
UNI 9175 Classe 1 IM
BS 476 Part 7 Class 1 – gültig für Xtreme (Adhered)
Bemerkung: Die Schwerentflammbarkeit hängt von den verwendeten Komponenten ab.

Lichtechtheit

6 (ISO 105 - B02)

Reibechtheit

Nass: 4, Trocken: 4 (ISO 105 - X12)

Reinigung

Waschbar bis 60°C. Regelmässig staubsaugen.
Dazu mit einem feuchten Tuch abwischen, oder
mit einem speziellen Polsterschaum behandeln.

UK

Composition

100% post-consumer recycled polyester

Environment

Certified to the EU Ecolabel
Certified to OEKO-TEX® Standard 100
Certified to Indoor Advantage™ Gold
Made from 100% recycled polyester
Non metallic dyestuffs

Width

140 cm minimum

Weight

310 g/m² ±5% [435 g/lin.m ±5%]

Abrasion Resistance

Heavy duty / 10 year guarantee
Independently certified to >100,000
Martindale cycles

Flammability

EN 1021 - 1 (cigarette)
EN 1021 - 2 (match)
BS 7176 Low Hazard
BS 5852 Ignition Source 5
BS 7176 Medium Hazard
DIN 4102 B1
NF D 60-013
ÖNORM B 3825 & A 3800-1 – only for Xtreme
UNI 9175 Classe 1 IM
BS 476 Part 7 Class 1 – only for Xtreme (Adhered)
Note: Flammability performance is dependent on components used.

Light Fastness

6 (ISO 105 - B02)

Fastness to Rubbing

Wet: 4, Dry: 4 (ISO 105 - X12)

Cleaning

Washable to 60°C. Vacuum regularly.
Wipe clean with a damp cloth or shampoo
using proprietary upholstery shampoo.

mauser 
Sitzkultur

Mauser Sitzkultur GmbH & Co.KG
Erlengrund 3
34477 Twistetal-Berndorf
Germany
T +49(0)5631 50514-0
F +49(0)5631 50514-44
info@mauser-sitzkultur.com
www.mauser-sitzkultur.com



Zertifiziert nach DIN EN ISO 9001 und 14001

 Made in Germany